



BMS 200-RBOV

Technical Features

<i>Pre-load (kgf)</i>	10
<i>Test Loads (kgf)</i>	60, 100, 150 (Rockwell), 62.5, 187.5 (Brinell), 30 (Vickers).
<i>Load Selection</i>	By load selector disc
<i>Test Method</i>	Rockwell, Brinell, Vickers
<i>Load Application</i>	Hydraulic
<i>Mang.of measuring microscope</i>	75xBrinell , 150xVickers
<i>Max Test Height</i>	With sliding table 140 mm Without sliding table 280 mm
<i>Depth of Throat</i>	145 mm
<i>Machine Dimensions</i>	780x490x170 mm
<i>Case Dimensions</i>	950x700x350 mm
<i>Weight (net/gross)</i>	95 / 125 kg
<i>Power Supply</i>	220V, 50HZ

Standart Accessories

<i>Rockwell Diamond Identor</i>	<i>1</i>
<i>1/16" Ball Indentor</i>	<i>1</i>
<i>HRC Test Block</i>	<i>1</i>
<i>HRB Test Block</i>	<i>1</i>
<i>Flat Testing Table</i>	<i>1</i>
<i>V Testing Table</i>	<i>1</i>
<i>Hardness Conversion Table</i>	<i>1</i>
<i>Case for Accessories</i>	<i>1</i>
<i>Allen Spanner</i>	<i>1</i>
<i>Instruction Manual</i>	<i>1</i>
<i>Calibration Certificate</i>	<i>1</i>
<i>Vickers Pyramid Indentor</i>	<i>1</i>
<i>2,5mm Ball Indentor</i>	<i>1</i>
<i>HB 2,5/187,5 Test Block</i>	<i>1</i>
<i>Vickers Test Block</i>	<i>1</i>