



BMS 3000-OB

Technical Specifications

<i>Loads (kgf)</i>	<i>500 to 3000 in Stage of 250</i>
<i>Max. Test Height (mm)</i>	<i>380</i>
<i>Depth of Throat (mm)</i>	<i>200</i>
<i>Size of Base (Sq. mm)</i>	<i>400 x 686</i>
<i>Machine Height (mm)</i>	<i>1250</i>
<i>Drive Motor (H.P.)</i>	<i>0.33</i>
<i>Mains Supply (V/Hz/Ph)</i>	<i>400-440/50/3</i>
<i>Optical Device</i>	<i>Direct reading optical device with 14x magnification.</i>
<i>Gross weight (kg)</i>	<i>350 (Approx.)</i>
<i>Diameter of balls used for indentation (mm)</i>	<i>10 or 5</i>
<i>Max. diameter of indentation which can be measured on Screen (mm)</i>	<i>8</i>
<i>Least Count of measuring device (mm)</i>	<i>0.01</i>
<i>Oil used for Hydraulic system</i>	<i>Servo system 32</i>

Standart Accessories

Testing Table __200 mm, for flat specimen	1
Testing Table 70 mm with 'V' groove for round jobs __10 mm to 80 mm	1
Ball holder 5 mm	1
Ball holder 10 mm	1
Test Block HB 5 / 750	1
Test Block HB 10 / 3000	1
Allen Spanner	4
Instruction Manual	1
Steel ball10 mm	5
Steel ball 5 mm	5
Tommy bar for fixing / removing extension	1
DIE spanner	2