



DIGIROCK RBOV

Technical Features

<i>Pre-load(kgf)</i>	10
<i>Loads (kgf)</i>	60,100,150 kgf Rockwell 62.5 ,187.5 kgf Brinell 30 kgf Vickers
<i>Load selection</i>	By load selector disc
<i>Test methods</i>	Rockwell,Brinell & Vickers
<i>Load application</i>	Hydraulic
<i>Max.testing height</i>	With sliding table 140 mm , without sliding table 240 mm
<i>Throat</i>	145 mm
<i>Machine dimensions</i>	780X550X360 mm
<i>Case dimensions</i>	950x700x350 mm
<i>Weight (net/gross)</i>	95 / 125 kg
<i>Optical System</i>	75X magnification for Brinell 150X magnification for Vickers
<i>Power</i>	220 V, 50Hz

Standart Accessories

<i>Rockwell Diamond cone indenter</i>	<i>1</i>
<i>Vickers Diamond pyramide indenter</i>	<i>1</i>
<i>1/16" ball indenter</i>	<i>1</i>
<i>2.5mm ball indenter</i>	<i>1</i>
<i>HRC test block</i>	<i>1</i>
<i>HRB test block</i>	<i>1</i>
<i>HB 2.5 / 187.5 Brinell test block</i>	<i>1</i>
<i>Flat testing table</i>	<i>1</i>
<i>V anvil for round parts</i>	<i>1</i>
<i>Hardness Conversion Table</i>	<i>1</i>
<i>Wooden case for accessories</i>	<i>1</i>
<i>Cover</i>	<i>1</i>
<i>Allen spanners</i>	<i>2</i>
<i>Operational Manual</i>	<i>1</i>
<i>Calibration Certificate</i>	<i>1</i>